

# LINE SSL PT



FINISH COLORS:




## LINE SSL PT 3000K

dimensions (mm)	number of LED modules	value $\phi$ (lm) per Led module					
		450/650/780 (lm)		940/1100/1250 (lm)		1500/1800/2000 (lm)	
a	b	code	power of system (W)	code	power of system (W)	code	power of system (W)
572	570	SSLP8041-T	5,5 / 8,0 / 9,5	SSLP8055-T	11,5 / 13,5 / 15,3	SSLP8069-T	18,4 / 22,1 / 24,5
855	853	SSLP8043-T	8,3 / 12,0 / 14,3	SSLP8057-T	17,3 / 20,3 / 23,0	SSLP8071-T	27,5 / 33,2 / 36,8
1138	1136	SSLP8045-T	11,0 / 16,0 / 19,0	SSLP8059-T	23,0 / 27,0 / 30,6	SSLP8073-T	36,8 / 44,2 / 49,0
1421	1419	SSLP8047-T	13,8 / 20,0 / 23,8	SSLP8061-T	28,8 / 33,8 / 38,3	SSLP8075-T	46,0 / 55,3 / 61,2
1704	1702	SSLP8049-T	16,5 / 24,0 / 28,5	SSLP8063-T	34,5 / 40,5 / 46,0	SSLP8077-T	55,0 / 66,0 / 74,0
1987	1985	SSLP8051-T	19,3 / 28,0 / 33,3	SSLP8065-T	40,0 / 47,0 / 53,5		
2270	2268	SSLP8053-T	22,1 / 32,0 / 38,1	SSLP8067-T	46,0 / 54,0 / 61,0		

## LINE SSL PT 4000K

dimensions (mm)	number of LED modules	value $\phi$ (lm) per Led module					
		450/650/780 (lm)		940/1100/1250 (lm)		1500/1800/2000 (lm)	
a	b	code	power of system (W)	code	power of system (W)	code	power of system (W)
572	570	SSLP8042-T	5,5 / 8,0 / 9,5	SSLP8056-T	11,5 / 13,5 / 15,3	SSLP8070-T	18,4 / 22,1 / 24,5
855	853	SSLP8044-T	8,3 / 12,0 / 14,3	SSLP8058-T	17,3 / 20,3 / 23,0	SSLP8072-T	27,5 / 33,2 / 36,8
1138	1136	SSLP8046-T	11,0 / 16,0 / 19,0	SSLP8060-T	23,0 / 27,0 / 30,6	SSLP8074-T	36,8 / 44,2 / 49,0
1421	1419	SSLP8048-T	13,8 / 20,0 / 23,8	SSLP8062-T	28,8 / 33,8 / 38,3	SSLP8076-T	46,0 / 55,3 / 61,2
1704	1702	SSLP8050-T	16,5 / 24,0 / 28,5	SSLP8064-T	34,5 / 40,5 / 46,0	SSLP8078-T	55,0 / 66,0 / 74,0
1987	1985	SSLP8052-T	19,3 / 28,0 / 33,3	SSLP8066-T	40,0 / 47,0 / 53,5		
2270	2268	SSLP8054-T	22,1 / 32,0 / 38,1	SSLP8068-T	46,0 / 54,0 / 61,0		



HOUSING:



MONTAGE:



DIFFUSER:



OPTICS/ROTATION:



LIGHT SOURCE:



POWER SUPPLY:



CONTROL:



NORMS:

